

FinishPro™ II PC Pro

Compact High Performance Air-Assisted Airless Sprayers with On-Board Compressor for a High-End Finish



PROFESSIONAL ADVANTAGES

- 2 in 1: combine the advantages of Air-Assisted Airless and Airless spraying with one unit Top HVLP finishing at the speed of Airless, without dillution
- "Green" SmartComp™ on-board compressor that only runs when air is needed: saving energy, reducing wear and noise
- Finish every job, every day thanks to ProConnect™ fast pump replacement system



FinishPro™ II PC Pro

Finish every job, every day!

FinishPro" II electric fine finish sprayers offer innovative features in a portable, self-contained, Air-Assisted Airless system. All sprayers are equipped with the ultra light G40" gun, Super-Flex" hose set, on-board compressor and Graco's proven piston pump technology.

"Plug and Spray" 2 in 1 Sprayer

Switch from Airless to Air-Assisted technology, just by flipping the switch. Spray in Air-Assisted mode using the perfect air, delivered by a smart compressor that only runs if air is needed, saving electricity and reducing wear.

FinishPro™ II 295 is designed for occasional finishing, small cabinet shops and enthusiast woodworkers.

The **FinishPro™ II 395 PC** and **595 PC Pro** true 2 in 1 sprayers allow high-quality finish work as well as pure airless spraying of walls and ceilings at residential and commercial projects with minimum overspray. Both sprayers are equipped with the ProConnect™ easy pump removal system.

The **FinishPro™ II 595 PC Pro** has a maintenance free brushless motor. In combination with the FastFlush™ cleaning system, this unit has enough power (2.6 L) to spray many exterior paints. It is the ideal unit for large commercial projects in combination with occasional façade painting.





Materials & Applications

The FinishPro is the ideal unit for larger fine finish jobs.

The FinishPro has been tested and approved to spray a wide range of lacquers, acrylic, primers, enamels, varnishes and acrylic interior paints, out of the bucket.

The ideal unit for renovation of cabinets, lighting features, shutters, fences, trims, stairs, staircases, or for painting doors, walls, decks and ceilings.





- Gun filter, integrated into the gun to minimize tip clogs
- Air adjustment valve, built into the gun
- Air cap with flat tip, extremely fine finish reduces overspray
- RAC tip conversion kit, to spray wall paint

(standard on the FinishPro II PC 395 and the FinishPro II PC Pro 595; optional on the FinishPro II 295)



Features



Exchange your pump easily **YOURSELF** in 3 steps in case any damage appear.

No more time wasted or money lost to labour charges on pump repairs.



Loosen the clamping nut



Open door and remove pump



GOOD TO KNOW

AIR-ASSISTED AIRLESS versus AIRLESS

AIR-ASSISTED AIRLESS

When spraying Air-Assisted Airless, material is delivered to the gun at pressure lower than traditional Airless (50-110 bar) and is partially atomised by the tip. Full atomisation is achieved by adding a small amount of air to the edges of the spray fan.

BENEFIT

Air-Assisted Airless spraying results in a softer pattern, more control, higher efficiency and ... less overspray, almost at the speed of an Airless unit.

More speed?

With the flip of one switch, the finisher turns into an Airless sprayer.



AIRLESS

When spraying airless with an Airless pump, fluid gets transferred from your paint bucket to the gun, simply by putting the paint under pressure (160-230 bar).

BENEFIT

Airless spraying is fast and paints can be sprayed without thinning.



! TIP

With a spare pump ready, you'll always be able to finish your job!



Fast Pump Replacement

- 1-minute job site replacement
- Keeps you spraying instead of waiting for service
- No pins or parts to lose!





FinishPro™ II Accessories

Get the most out of your equipment, using our professional accessories

Improve your finishing quality



G40™ Guns

Air-, flow- and fan-adjustment, 100 mesh gun filter, tip and guard 262932 Flat tip AAM309 (incl. fan regulator) 262929 RAC tip FFA210 (no fan regulator)



Super-Flex™ Fluid and Air Hose Set

Including 2 m whip

24U578 24U579 7.5 m 15 m



Fluid and Air Hoses

G40 gun, tip, whip, Super-Flex™ fluid and air hose kit 24V155 Delivered with 262932 + 24U578 24V156 Delivered with 262929 + 24U579



Super-Flex[™] Whip Hose

278750 1/8" x 2 m (fluid)



Flex Wrap Hose Protector

24U576 24U577 $7.5 \, \text{m}$ 15 m



ProGuard™+

24W090 230V, CEE 7/7, shuko 24W755 230V, IEC320, multicord



Blister Pack - ProConnect Pump Lower

17C489 Blister Pack, fits only FinishPro II 395 PC

and FinishPro II 595 PC Pro



Hopper Assembly 5.7 liter

24B250 Hopper



RAC X™ Tip Extensions

287019 25 cm 287020 40 cm 50 cm 287021 75 cm 287022



JetRoller™ System 0.5 m Heavy Duty Extension

roller 18 cm

roller 25 cm

with Inline™ Gun without Inline™ Gun 24V490 roller 18 cm 24V492 24V491 roller 25 cm 24V493

232123 1 m Heavy Duty extension



287026 90 cm 287027 180 cm



Tips & Guards

FFAXXX Green RAC X fine finish tip **PAAXXX** Blue RAC X professional airless tip

AAMXXX Flat AA tip with SST body



Filters G40 Gun Filters (5-pack)

224454 60 mesh 224453 100 mesh

FinishPro II 295

257094 Easy Out Inline filter, 40 mesh FinishPro II 395/595 Easy Out™ Manifold Filter



246384 60 mesh. black 246382 100 mesh, bleu

246383 200 mesh. red FinishPro II 295/395/595

246385 Pump inlet strainer



Disposable, Inline Desiccant Air Filter 127465 Single 24U981





Various

288839 G40 RAC X air cap

288514 Conversion kit (RAC to flat) 24U616 Conversion kit (flat to RAC) 249256 Guard for AAM flat tip Air cap for AAM flat tip 249180



Specifications

ALL UNITS SHIP WITH an on-board compressor, G40™ gun (including air cap and tip),







5-pack

Super-riex find and air nose kit (including whip nose) and flex nose wrap.			00-16
	FinishPro II 295	FinishPro II 395 PC	FinishPro II 595 PC Pro
Part Numbers: for EURO / Multicord version (230 V)	24U061 / 24U062	17C418 / 17C421	17C423 / 17C358
for UK (110 V)	_	17C320	_
Max. Working Pressure - bar (PSI)	207 (3000)	230 (3300)	230 (3300)
Max. Fluid Flow - I/min. (gpm)	1.3 (0.34)	2.0 (0.47)	2.6 (0.68)
Max. Tip Size - 1 gun	0.017"	0.023"	0.027"
Weight - kg (lbs)	31 (68)	50 (110)	51 (112)
Motor Rating - HP (DC) / Minimum Generator Requirement - W	1/2 Brush / 3000	7/8 TEFC Brush / 4000	1.4 Brushless / 4000
Compressor Output	3.2 cfm at 35 psi	3.2 cfm at 35 psi	3.2 cfm at 35 psi
Features: G40™ gun	Flat tip and guard	Flat tip and guard	Flat tip and guard
Flat to RAC™ Conversion Kit	_	✓	✓
Tips	AAM309	AAM309 / FFA210 / PAA517	AAM309 / FFA210 / PAA517
Fluid Hose + Fluid Whip Hose	1/4" x 7.5m + 1/8" x 2m	1/4" x 7.5m + 1/8" x 2m	1/4" x 15m + 1/8" x 2m
Air Hose + Air Whip Hose	3/8" x 7.5m + 1/4" x 2m	3/8" x 7.5m + 1/4" x 2m	3/8" x 15m + 1/4" x 2m
SmartComp [™] / ProConnect [™] / FastFlush [™] / Water Separator Kit	-/-/-/-	√ / √ /—/—	111111
Gun / Pump Filter - mesh	100	100/100	100/100
SmartControl™ version	_	1.0	2.5